

RDM  
Control

Flicker Free

Drama 300C Profile is a RGBAL LED light . Lens available at 19°, 26°, 36°, 50°. HD optics and four shutters to control the shape of the light. Fixture also equipped with powercon in & out connector.


#### Key features:

- RGBAL LED
- HD optical system, clean shutter cuts beam
- 19°, 26°, 36°, 50° lens optional
- Smooth dimming, flicker free operation
- Flicker free with selectable PWM
- DMX control of dimmer
- Aluminum housing, robust construction
- No fan, ultra quiet


#### Application:

- Broadcast, HD studio
- Theatre, church
- Fashion show
- Museum
- Exhibition lighting

#### Accessories:



Gel frame



Gobo holder (opt.)

## Drama 300C Profile

### 300W RGBAL LED profile



#### Technical Data

Power supply:	AC100 - 240V, 50/60Hz
Light source:	60W R + 60W G + 60W B + 60W A + 60W L
Color temperature:	2500K - 8000K tunable
Fixed lens:	19°, 26°, 36°, 50°
Color Rendition:	CRI 95
Power connection:	PowerCON in & out
Signal connection:	3-pin XLR in & out(5-pin opt.)
Control channels:	6/10CH

Housing:	Color black, aluminum
Size:	660*235*280mm
Control mode:	DMX, RDM
N.W.:	11.7kg
Accessories(incl.):	Power cable, Gel frame, Safety rope
Accessories(opt.):	Gobo holder, Clamp
Environment:	IP65

